
robby Documentation

Release 0.1.0

Simon de Haan

Nov 01, 2018


Contents

1	Robby	3
1.1	API	3
2	Installation	5
3	Usage	7
4	Contributing	9
4.1	Types of Contributions	9
4.2	Get Started!	10
4.3	Pull Request Guidelines	11
4.4	Tips	11
5	Credits	13
5.1	Development Lead	13
5.2	Contributors	13
6	History	15
7	0.1.0 (2015-01-11)	17
8	Indices and tables	19

Contents:

CHAPTER 1

Robby

Probabilities as a Service  Available as a docker container with `docker pull sdehaan/robby`. The docker container allow the for the following environment variables:

- REDIS_HOST, defaults to 127.0.0.1
- REDIS_PORT, defaults to 6379
- REDIS_DB, defaults to 1
- ROBBY_PORT, defaults to 8080
- ROBBY_PREFIX, the prefix for Redis keys, defaults to robby
- ROBBY_STEMMING_LANGUAGE, defaults to english
- ROBBY_TOKENIZER, the python callable to use for tokenizing. Defaults to `robby.utils.english_tokenizer`, `robby.utils.dumb_tokenizer` is also available.

Or `pip install robby` and run directly:

```
robby \  
  --redis-uri redis://127.0.0.1:6379/1 \  
  --interface 0.0.0.0 \  
  --port 8080 \  
  --prefix robby \  
  --stemming \  
  --stemming-language=english \  
  --tokenizer=robby.utils.english_tokenizer \  
  --debug
```

1.1 API

To train it:

```
$ curl -d 'training sample' http://localhost:8080/train/bucket-name/category
```

To untrain it:

```
$ curl -d 'training sample' http://localhost:8080/untrain/bucket-name/category
```

To train it in batches:

```
$ curl -d '[{"category": "category", "content": "training sample"}]' http://  
→localhost:8080/batch/train/bucket-name
```

To classify:

```
$ curl -d 'sample message' http://localhost:8080/classify/bucket-name  
{  
  "category": "category"  
}
```

To get scoring:

```
$ curl -d 'sample message' http://localhost:8080/score/bucket-name  
{  
  "category": 0.01  
}
```

To get clear the db:

```
$ curl -X DELETE http://localhost:8080/flush/bucket-name
```


CHAPTER 2

Installation

At the command line:

```
$ easy_install robbly
```

Or, if you have virtualenvwrapper installed:

```
$ mkvirtualenv robbly  
$ pip install robbly
```


CHAPTER 3

Usage

To use robbly in a project:

```
import robbly
```


Contributions are welcome, and they are greatly appreciated! Every little bit helps, and credit will always be given. You can contribute in many ways:

4.1 Types of Contributions

4.1.1 Report Bugs

Report bugs at <https://github.com/smn/robby/issues>.

If you are reporting a bug, please include:

- Your operating system name and version.
- Any details about your local setup that might be helpful in troubleshooting.
- Detailed steps to reproduce the bug.

4.1.2 Fix Bugs

Look through the GitHub issues for bugs. Anything tagged with “bug” is open to whoever wants to implement it.

4.1.3 Implement Features

Look through the GitHub issues for features. Anything tagged with “feature” is open to whoever wants to implement it.

4.1.4 Write Documentation

robby could always use more documentation, whether as part of the official robby docs, in docstrings, or even on the web in blog posts, articles, and such.

4.1.5 Submit Feedback

The best way to send feedback is to file an issue at <https://github.com/smn/robby/issues>.

If you are proposing a feature:

- Explain in detail how it would work.
- Keep the scope as narrow as possible, to make it easier to implement.
- Remember that this is a volunteer-driven project, and that contributions are welcome :)

4.2 Get Started!

Ready to contribute? Here's how to set up *robby* for local development.

1. Fork the *robby* repo on GitHub.
2. Clone your fork locally:

```
$ git clone git@github.com:your_name_here/robby.git
```

3. Install your local copy into a virtualenv. Assuming you have virtualenvwrapper installed, this is how you set up your fork for local development:

```
$ mkvirtualenv robby
$ cd robby/
$ python setup.py develop
```

4. Create a branch for local development:

```
$ git checkout -b name-of-your-bugfix-or-feature
```

Now you can make your changes locally.

5. When you're done making changes, check that your changes pass flake8 and the tests, including testing other Python versions with tox:

```
$ flake8 robby tests
$ python setup.py test
$ tox
```

To get flake8 and tox, just pip install them into your virtualenv.

6. Commit your changes and push your branch to GitHub:

```
$ git add .
$ git commit -m "Your detailed description of your changes."
$ git push origin name-of-your-bugfix-or-feature
```

7. Submit a pull request through the GitHub website.

4.3 Pull Request Guidelines

Before you submit a pull request, check that it meets these guidelines:

1. The pull request should include tests.
2. If the pull request adds functionality, the docs should be updated. Put your new functionality into a function with a docstring, and add the feature to the list in README.rst.
3. The pull request should work for Python 2.6, 2.7, 3.3, and 3.4, and for PyPy. Check https://travis-ci.org/smn/robby/pull_requests and make sure that the tests pass for all supported Python versions.

4.4 Tips

To run a subset of tests:

```
$ python -m unittest tests.test_robby
```


5.1 Development Lead

- Simon de Haan <simon@praekeltfoundation.org>

5.2 Contributors

None yet. Why not be the first?

CHAPTER 6

History

CHAPTER 7

0.1.0 (2015-01-11)

- First release on PyPI.

CHAPTER 8

Indices and tables

- `genindex`
- `modindex`
- `search`